


Module - Air Bag - Deploy (Outside the Vehicle) (40 702 0)

Special Tools



40-007Deployment/Test lead

Material

12V vehicle battery	
---------------------	--

Remove



WARNING:


WAIT AT LEAST 15 MINUTES AFTER DISCONNECTING THE BATTERY BEFORE DISCONNECTING THE AIR BAG CONTROL MODULE ELECTRICAL CONNECTOR. FOR ALL OTHER SUPPLEMENTARY RESTRAINTS SYSTEM ELECTRICAL CONNECTORS; WAIT TWO MINUTES. FAILURE TO FOLLOW THESE PROCEDURES COULD INCREASE THE POSSIBILITY OF ACCIDENTLY DEPLOYING THE AIR BAG(S) AND PYROTECHNIC PRETENSIONERS.



CAUTION:

Disconnect the battery negative lead.

1. Remove the air bag module to be deployed (refer to Section 40-03).




WARNING:

DO NOT DEPLOY AIR BAG(S) UNLESS THE COVER SIDE IS FACING UPPERMOST.

2. Connect the appropriate adaptor lead from the Special Tool 40-007 to the air bag module (Mondeo shown).


- 1 Drivers air bag module.
- 2 Passenger air bag module.
- 3 Fiesta, Escort, Mondeo, Scorpio and Galaxy air bag adaptor leads.
- 4 Pyrotechnic belt pretensioner adaptor lead.
- 5 Galaxy passenger air bag adaptor lead.
- 6 Maverick adaptor lead.
- 7 Probe adaptor lead.




CAUTION:

To protect the adaptor lead connector from damage during deployment, raise the air bag off the ground on the two wooden blocks.

3. Place the air bag inside a wire cage (e.g. overturned roller container) with the air bag cover facing uppermost.




4. Connect the deployment lead to the adaptor lead.



WARNING:

BEFORE PROCEEDING TO STEP 6 ENSURE THAT ALL THE PERSONNEL WORKING IN THE VICINITY ARE AWARE OF THE FACT THAT A LOUD NOISE (BANG) IS ABOUT TO OCCUR. DO NOT LET ANYBODY APPROACH CLOSER THAN SIX METRES.

5. Connect the crocodile clips to the battery.



WARNING:

THE AIR BAG SHOULD NOT BE HANDLED IMMEDIATELY FOLLOWING DEPLOYMENT AS THE AIR BAG MODULE WILL BE VERY HOT. WAIT FOR 30 MINUTES BEFORE DISPOSING OF THE MODULE IN A SEALED BAG. USE PROTECTIVE GLOVES WHEN HANDLING DEPLOYED UNIT.

6. Deploy the air bag.
- Depress both switches.
-