


Bumper Assembly - Front - Remove And Install (43 423 0)


Remove



CAUTION:
Disconnect the battery negative lead.




1. Remove the Torx retaining screws (four screws).




(Up To '93 MY)

2. Lift and remove the grille.



Grille - Radiator ('95½ My Onwards) - Remove (43 232 0)


3. Remove the air deflector (four clips and four Torx screws).




CAUTION:

Care should be taken not to damage paintwork when securing the radiator.


4. Secure the radiator to the hood slam panel.
5. Raise the vehicle.



6. Remove the left and right-hand lower wheelhouse liner extension (five screws each side).




7. Detach the hose and cable from the right-hand radiator support.




Vehicles fitted with Air Conditioning


8. Detach the A/C condenser.




9. Remove the splash shield nuts.




- ➡ 10. Carefully prise down the splash shield and remove the nuts (one each side).



- ➡ 11. Remove the left and right-hand radiator support (four bolts).




- ➡ 12. Remove the bumper retaining screws from the left and right-hand wheelhouse.




CAUTION:

When disconnecting the multiplug do not pull on the wiring; pull on the multiplug body.

- ⌚ 13. Disconnect the multiplugs on the bumper mounted lamps.



- ⌚ 14. Remove the bumper retaining nuts (four nuts).



- ⌚ 15. Remove the bumper assembly.

Install

16. Refit the components in reverse order.
 Grille - Radiator (Up To '93 MY) - Install (43 232 0)
 Grille - Radiator ('95½ MY Onwards) - Install (43 232 0)
